



Akasil[®] Antifoam TG 20

Silicone antifoam emulsion

Description

Akasil[®] Antifoam TG20 is a silicone based antifoam emulsion. The active content is 22%.

Application

Akasil[®] Antifoam TG20 is a highly effective, water soluble silicone based antifoam emulsion which has been developed specifically for technical applications.

Features

- Outstanding reliability and versatility.
- Suitable for products with high salinity.
- Available in easy-to-use emulsion form.
- Good high temperature performance.

Benefits

- Excellent knockdown as well as defoaming performance.
- Highly effective enabling attainment of foam control with minimal addition of non-nutrient additives

Typical Data

Parameter	Unit	Value
Appearance		white liquid
Active content	%	22
Specific gravity by 25° C		1.0
pH		5 - 9
Recommended diluent		soft/deionized water

Warranty: The information given in this product data sheet are believed to be fully accurate. However, BRB International BV shall not be liable for its content and make no warranty with respect thereto. For additional information we request you to contact BRB International BV visit our web-site: www.brb-international.com



How to Use

The antifoam disperses easily in both hot and cold aqueous systems, requiring only mild agitation to disperse it completely in the foaming system. For maximum efficiency and economy, however, we recommend the antifoam be pre-diluted with water before use, in the ratio of one volume of *Akasil® Antifoam TG20* to four volumes of cool soft or deionised water, the water being added slowly to the antifoam with continual low shear agitation. The diluted antifoam should be used with twelve hours of dilution for best results. The quantity of *Akasil® Antifoam TG20* required to control foaming can only be found by experiment. In general, between 0.01 and 0.5 g/l of as supplied antifoam is all that is required. Apart from storing the emulsion under reasonably cool conditions, no special storage precautions need to be taken..